

AMENDMENT

Following entry of this amendment, claims 1-21 and 34-40 remain pending in the application.

In the Claims

In accordance with 37 C.F.R. § 1.121(c), a marked-up version of each amended claim, showing all the changes made relative to the previous version, is set forth in Attachment One hereto, and the following amended claims are submitted:

15. A mold assembly for use in manufacturing molded thermoplastic containers comprising:
two mold shells each containing a half-impression of a substantial portion of the container to be molded;
two mold shell holders each defining a cavity for receiving each said respective mold shell such that each said respective mold shell is in at least partial mutual thermal-conduction contact with its respective shell holder, said shell holders being shaped to be supported by two mold carriers made in the form of enveloping structures; and
at least one quick-fixing locking member by which at least one of said mold shells is removably secured to a respective one of said mold shell holders, said one quick-fixing locking member including a selectively retractable locking member portion.

23 35. A mold assembly for use in manufacturing molded thermoplastic containers comprising:
two mold shells each containing a half-impression of a substantial portion of the container to be molded;
two mold shell holders each defining a cavity for receiving each said respective mold shell such that each said respective mold shell is in at least partial mutual thermal-conduction contact with its respective shell holder, said shell holders being shaped to be supported by two mold carriers made in the form of enveloping structures; and
at least one quick-fixing locking member by which at least one of said mold shells is removably secured to a respective one of said mold shell holders, said quick-fixing locking member itself including a retractable locking member portion which can be selectively extended and retracted such that when extended, said retractable locking member portion provides at least partial

securement of said one of said mold shells relative to said corresponding mold shell holder, and when retracted, said retractable locking member portion does not provide securement of said one said mold shells relative to said corresponding mold shell holder.

50b 24 37
36. A mold assembly for use in manufacturing molded thermoplastic containers comprising:

two mold shells each containing a half-impression of a substantial portion of the container to be molded;

two mold shell holders each defining a cavity for receiving each said respective mold shell such that each said respective mold shell is in at least partial mutual thermal-conduction contact with its respective shell holder, said shell holders being shaped to be supported by two mold carriers made in the form of enveloping structures; and

at least one quick-fixing locking member by which at least one of said mold shells is removably secured to a respective one of said mold shell holders, said one quick-fixing locking member including a selectively movable locking member portion which can be selectively moved into and out of a locking position which at least partially locks said one of said mold shells to said respective mold shell holder, and said quick-fixing locking member is configured to include a portion which remains engaged with said mold shell holder when said quick fixing locking member is moved out of said locking position.

50b 21 39 47
37. A mold assembly for use in manufacturing molded thermoplastic containers comprising:

two mold shells each containing a half-impression of a substantial portion of the container to be molded;

two mold shell holders each defining a cavity for receiving each said respective mold shell such that each said respective mold shell is in at least partial mutual thermal-conduction contact with its respective shell holder, said shell holders being shaped to be supported by two mold carriers made in the form of enveloping structures; and

at least one quick-fixing, slidable lock by which at least one of said mold shells is removably secured to a respective one of said mold shell holders, said slidable lock being slidable into and out of a locking position which at least partially locks said one of said mold shells relative to said respective mold shell holder.